## **Toll / Fast Barrier**



Registered with MSME (Govt. of India) Powered by Alaska Automation Pvt. Ltd. **An ISO 9001:2015 Company** 

MOSFI India's No.1 Manufacturer of Entrance Automation Product Present's

# TARPIDO

## EMBELLISH WITH GERMAN ENGINEERING



**SMART COLLISION** DETECTION TECHNOLOGY

**OPENINING SPEED 0.9sec** 

**SWING OUT MECHANISM** 

### **TARPIDO**



**An ISO 9001:2015 Company** 

#### Features:

100% duty cycle

24\*7\*365

#### SMART COLLISION DETECTION TECHNOLOGY

When boom collision with any obstacles it reverse to their opening position.





OPENINING SPEED 0.9sec

#### **SWING OUT MECHANISM**

When boom hit by vehicle it will leave automatically by their jack.






Integrate With Any Software Access Hardware, Toll Management Solution Weight Bridges, RFID Readers, Smart Cards Any Access Machine

#### TELESCOPIC SHOCK ABSORBER

It absorbe's absolutely all vibration which is created due to high speed of machine for long life & maintenance free barrier.





#### TRAFFIC LIGHTS

Can be integrate with any traffic lights, blinker lights.

#### MANUAL OPTION IN CASE OF POWER FAILURE

Barrier is equipped with manual handle if power failure or any obstacle.



### Specification:


MODEL NO	TARPIDO 200	TARPIDO 300	TARPIDO 600
OPEN/CLOSE TIME	0.98	1SEC	4SEC
LENGTH OF ARM	2 MTR	3 MTR	6 MTR
DUTY CYCLE	100%	100%	100%
ARM SWING HUB	80*45	80*45	80*45
PAINT TYPE	POWDER COATED	POWDER COATED	POWDER COATED
MOTOR SPEED	1400 RPM	1400 RPM	1400 RPM
MOTOR POWER	80W	80W	80W
MOTOR TYPE	AC MOTORS		
VOLTAGE	220V±10%,/110V±10%	220V±10%,/110V±10%	220V±10%,/110V±10%
FREQUENCY	50/60HZ	50/60HZ	50/60HZ
GEAR MATERIAL	ALMUNIUM, COPPER, MILDSTEEL	ALMUNIUM, COPPER, MILDSTEEL	ALMUNIUM, COPPER, MILDSTEEL
LIMIT SWITCHES	AVAIALBLE	AVAIALBLE	AVAIALBLE
CONTROLLER TYPE	FR-458 SERIES	FR-458 SERIES	FR-458 SERIES
BARRIER MATERIAL	MILD STEEL	MILD STEEL	MILD STEEL
BARRIER DIMENSION	335 * 335 * 935 Mm	335 * 335 * 935 Mm	335 * 335 * 935 Mm
BOOM MATERIAL	ALMUNIU (OCTOGONAL BOOM)	ALMUNIUM (OCTOGONAL BOOM)	ALMUNIUM (OCTOGONAL BOOM)
POWER FAILIURE	MANUAAL RELEASE	MANUAAL RELEASE	MANUAAL RELEASE
MTTR			
МТВ	6 BILLION CYCLE	6'BILLION CYCLE	6 BILLION CYCLE
RUNNING NOISE	45dB	45dB	45dB
WEIGHT	55 KG(APPROX)	55 KG(APPROX)	55 KG (APPROX)
TEMPRATURE	-40°C to + 75°C	-40°C to + 75°C	-40°C to + 75°C
HUMIDITY	5-90%	5-90%	5-90%
BOOM CONTROL			
Operation through	SPRING BALANCE	Intensive	Intensive
	Remote/E.switches/ all access system/manual	Remote/E.switches/ all access system/manual	Remote/E.switches/ all access system/manual

MOSFI India's No.1 Manufacturer of Entrance Automation Product Present's


## TARPIDO

### EMBELLISH WITH GERMAN ENGINEERING





- 1. Mainboard
- 2. Blance crank
- 3. Spindle curved balance boor
- 4. Spindle
- 5. Initiative crank
- 6. Curved rod
- 7. Boom tray head
- 8,9. Bearing bracket
- 10,11. Motor cabinet
- 12. Planet gear reducer
- 13. Serve motor
- 14. Limited block
- 15. Spring bracket
- 16. Spring sleeve
- 17. PVC tube
- 18. Compression spring
- 19. Adjusted screw rod
- 20. Spring plate
- 21. Spring adjusted handle
- 22. Boom



www.alaskagroup.in | sales@alaskagroup.in